

| Art. No. | Description | Specifications | Picture | Weight | Customs Tariff No. | C/O* | SL* | WL.* | SNo.* Stock* | WPC* | POH* | PU* | Sales price in \$ |
|----------|-------------------------------|---|---------|----------|-----------------------|------|-----|------|--------------|------|------|-------|-------------------|
| 1891 | Axis cable set (X, Y, Z, B) | consisting of: – axis cables (X, Y, Z, B) – control unit connector CUC 1 with 40 pins | | 0.950 lb | 84799070 | DE | S | | 1 | | - | 1 PCS | 603.00 |
| 2052 | Data cable Renfert SILENT CAM | plug with 6 pinslength 5 m | | 0.364 lb | 85087000 | DE | U | | - | | - | 1 PCS | 74.00 |
| 1884 | End switch | including mounting material | | 0.049 lb | 84818079 | CZ | S | | 2 | | - | 1 PCS | 48.00 |
| 2010 | Ethernet cable | length approx. 2.0 m | | 0.174 lb | 85444210 | CN | U | | 1 | | - | 1 PCS | 12.30 |

^{*} PU = packing unit | C/O = country of origin | SL = service level (U=user, S=service | WL = warranty limitation | SNo. = serial number required | Stock = stock recommendation * WPC = wear parts and consumables | POH = parts on hand (recommended minimum quantity for on site service calls)



| Art. No. | Description | Specifications | Picture | Weight Customs Tariff No. | C/O* | SL* | WL.* | SNo.* | Stock* | WPC* | РОН* | | Sales price in \$ |
|----------|--|--|---------|------------------------------|------|-----|------|-------|--------|------|------|-------|-------------------|
| 30288 | Ethernet socket | including mounting material | | 0.057 lb 84799070 | GB | S | | | - | | - | 1 PCS | 41.00 |
| 1832 | Glass fuse T6.3A L250V | PU 10 pieces | | 0.002 lb 84799070 | DE | U | | | - | | - | 1 PU | 9.60 |
| 30181 | Glass fuse T8.0A L250V | PU 10 pieces | | 0.035 lb 84799070 | DE | S | | | 1 | | 1 | 1 PU | 20.20 |
| 1890 | Interlock switch/LED boards with cable set | consisting of: - interlock switch - LED boards with cable - control unit connector CUC 2 with 28 pins | | 0.600 lb 84799070 | DE | S | | | 1 | | - | 1 PCS | 495.00 |

^{*} PU = packing unit | C/O = country of origin | SL = service level (U=user, S=service | WL = warranty limitation | SNo. = serial number required | Stock = stock recommendation * WPC = wear parts and consumables | POH = parts on hand (recommended minimum quantity for on site service calls)



| Art. No. | Description | Specifications | Picture | Weight | Customs Tariff No. | C/O* | SL* | WL.* | SNo.* Stock | * WPC* | РОН* | PU* | Sales price in \$ |
|----------|---------------------|---|---------|----------|-----------------------|------|-----|------|-------------|--------|------|-------|-------------------|
| 30117 | Ion jet left | including DC voltage converter and mounting material | | 0.500 lb | 84799070 | DE | S | | - | | - | 1 PCS | 439.00 |
| 30118 | Ion jet right | including mounting material | | 0.500 lb | 84799070 | DE | S | | - | | - | 1 PCS | 439.00 |
| 1903 | Measuring key | including mounting material | | 0.150 lb | 84798997 | СН | S | | 1 | X | 1 | 1 PCS | 581.00 |
| 1589 | Power supply cord B | connector plug up to 120 V plug type B length approx. 1.8 m UL certified | | 0.700 lb | 85444290 | | U | | 1 | | - | 1 PCS | 14.00 |

^{*} PU = packing unit | C/O = country of origin | SL = service level (U=user, S=service | WL = warranty limitation | SNo. = serial number required | Stock = stock recommendation * WPC = wear parts and consumables | POH = parts on hand (recommended minimum quantity for on site service calls)



| Art. No. | Description | Specifications | Picture | Weight | Customs Tariff No. | C/O* | SL* | WL.* SN | lo.* Stock* | WPC* | РОН* | PU* | Sales price in \$ |
|----------|-----------------------------|---|---------|----------|-----------------------|------|-----|---------|-------------|------|------|-------|-------------------|
| 1892 | Spindle cable | | | 0.450 lb | 84799070 | DE | S | | 1 | | - | 1 PCS | 344.00 |
| 30555 | Switching mode power supply | May only be replaced by a qualified electrician. After repair work the machine requires a test of the electrical safety according to VDE. | | 2.392 lb | 84799070 | DE | S | | 1 | | - | 1 PCS | 473.00 |
| 1612 | USB connecting socket | without mounting material | | 0.100 lb | 84799070 | DE | S | | - | | - | 1 PCS | 30.00 |
| 30119 | Webcam | including mounting material and protective cap | | 0.500 lb | 84799070 | DE | S | | - | | - | 1 PCS | 419.00 |

^{*} PU = packing unit | C/O = country of origin | SL = service level (U=user, S=service | WL = warranty limitation | SNo. = serial number required | Stock = stock recommendation * WPC = wear parts and consumables | POH = parts on hand (recommended minimum quantity for on site service calls)



Housings and Accessories

| Art. No. | Description | Specifications | Picture W | Veight | Customs Tariff No. | C/O* | SL* | WL.* | SNo.* Stock* | WPC* | РОН* | | Sales price in \$ |
|----------|---|----------------|-----------|----------|-----------------------|------|-----|------|--------------|------|------|-------|-------------------|
| 1889 | Gas spring 70 N | PU 2 pieces | | 0.200 lb | 84799070 | DE | S | | 1 | X | 1 | 1 PU | 151.00 |
| 1651 | Hinged actuator for door locking switch | | | 0.022 lb | 84799070 | JP | S | | 1 | | - | 1 PCS | 15.80 |

^{*} PU = packing unit | C/O = country of origin | SL = service level (U=user, S=service | WL = warranty limitation | SNo. = serial number required | Stock = stock recommendation * WPC = wear parts and consumables | POH = parts on hand (recommended minimum quantity for on site service calls)



| Art. No. | Description | Specifications | Picture | Weight Cust Tarit | oms C f No. | ;/O* | SL* | WL.* | SNo.* | Stock* | WPC* | РОН* | | Sales price in \$ |
|----------|---|-----------------------------|---------|----------------------|----------------|------|-----|------|-------|--------|------|------|-------|-------------------|
| 30477 | A-axis | | | 0.441 lb 8479 | 9070 | DE | S | Х | | - | | - | 1 PCS | 756.00 |
| 1881 | Anti-rotation lock axis motor B-axis | including mounting material | | 0.050 lb 8481 | 8079 I | DE | S | | | 2 | | - | 1 PCS | 57.00 |
| 1883 | Anti-rotation lock axis motor X-/Z-axis | including mounting material | | 0.050 lb 8481 | 8079 I | DE | S | | | 4 | | - | 1 PCS | 57.00 |
| 1882 | Anti-rotation lock axis motor Y-axis | including mounting material | | 0.050 lb 8481 | | DE | S | | | 2 | | - | 1 PCS | |

^{*} PU = packing unit | C/O = country of origin | SL = service level (U=user, S=service | WL = warranty limitation | SNo. = serial number required | Stock = stock recommendation * WPC = wear parts and consumables | POH = parts on hand (recommended minimum quantity for on site service calls)



| Art. No. | Description | Specifications | Picture | Weight Custom Tariff N | s C/O* | SL* | WL.* | SNo.* | Stock* | WPC* | РОН* | PU* | Sales price in \$ |
|----------|-------------------------|--|---------|---------------------------|--------|-----|------|-------|--------|------|------|-------|-------------------|
| 1880 | Axis motor | consisting of: - step motor with cylinder pin - damper mat | | 0.850 lb 8501109 | 1 CN | S | | | 4 | | - | 1 PCS | 229.00 |
| 2050 | Ball screw drive B-axis | including mounting material | | 1.500 lb 8479907 | 0 FR | S | X | | - | | - | 1 PCS | 1,610.00 |
| 2047 | Ball screw drive X-axis | including mounting material | | 0.800 lb 8479907 | 0 FR | S | X | | 1 | | - | 1 PCS | 1,280.00 |
| 2048 | Ball screw drive Y-axis | including mounting material | | 1.550 lb 8479907 | 0 FR | S | х | | 1 | | - | 1 PCS | 1,210.00 |

^{*} PU = packing unit | C/O = country of origin | SL = service level (U=user, S=service | WL = warranty limitation | SNo. = serial number required | Stock = stock recommendation * WPC = wear parts and consumables | POH = parts on hand (recommended minimum quantity for on site service calls)



| Art. No. | Description | Specifications | Picture | Weight Custo | oms C No. | C/O* | SL* | WL.* | SNo.* | Stock* | WPC* | РОН* | PU* | Sales price in \$ |
|----------|----------------------------------|---|---------|----------------|--------------|------|-----|------|-------|--------|------|------|-------|-------------------|
| 2049 | Ball screw drive Z-axis | including mounting material | | 0.800 lb 84799 | 070 | FR | S | X | | - | | - | 1 PCS | 1,130.00 |
| 1887 | Bellows | including mounting material | | 0.150 lb 84799 | 070 | DE | S | | | 1 | | - | 1 PCS | 393.00 |
| 30354 | Blank holder K5+/K5 | for tool-less blank mounting (DirectDiscTechnology) including mounting material | | 0.000 lb 84799 | 070 | DE | S | | | - | | - | 1 PCS | 2,430.00 |
| 30154 | Clamp ring for ball screw drives | including clamping screw | | 0.033 lb 84818 | 079 | DE | S | | | 1 | | 4 | 1 PCS | 17.20 |

^{*} PU = packing unit | C/O = country of origin | SL = service level (U=user, S=service | WL = warranty limitation | SNo. = serial number required | Stock = stock recommendation * WPC = wear parts and consumables | POH = parts on hand (recommended minimum quantity for on site service calls)



| _ | Description | Specifications | Picture | Weight | Customs | C/O* | SL* | WL.* | SNo.* Stock* | WPC* | POH* | PU* | Sales |
|-------|--|---|---------|----------|------------|------|-----|------|--------------|------|------|-------|-------------|
| | | | | | Tariff No. | | | | | | | | price in \$ |
| 1970 | Concentricity test pin | to adjust the concentricity of ball screw drives | | 0.050 lb | 84799070 | DE | S | | - | | 1 | 1 PCS | 47.00 |
| 30365 | Double cone locking mechanism blank holder K5+ | PU 2 pieces | | 0.000 lb | 84799070 | DE | S | | - | | - | 1 PU | 87.00 |
| 1570 | Fixing insert for tool changer | rubber inserts for tool changerPU 2 pieces | | 0.050 lb | 84799070 | DE | U | | 5 | X | 1 | 1 PU | 20.50 |
| 1886 | Folding bellow X-axis (215 mm length) | PU 2 pieces | | 0.220 lb | 84799070 | DE | S | | 1 | | - | 1 PU | 213.00 |

^{*} PU = packing unit | C/O = country of origin | SL = service level (U=user, S=service | WL = warranty limitation | SNo. = serial number required | Stock = stock recommendation * WPC = wear parts and consumables | POH = parts on hand (recommended minimum quantity for on site service calls)



| Art. No. | Description | Specifications | Picture | Weight | Customs Tariff No. | C/O* | SL* | WL.* | SNo.* Stock* | WPC* | РОН* | PU* | Sales price in \$ |
|----------|---------------------------------------|--|---------|----------|-----------------------|------|-----|------|--------------|------|------|-------|-------------------|
| 1885 | Folding bellow Y-axis (300 mm length) | PU 2 pieces | | 0.430 lb | 84799070 | DE | S | | 1 | | - | 1 PU | 295.00 |
| 1894 | Front cover stop | including mounting materialPU set of 2 pieces | | 0.050 lb | 84799070 | DE | S | | 1 | | - | 1 PU | 22.90 |
| 1897 | Hinged actuator retainer | including mounting material | | 0.180 lb | 84798997 | DE | S | | - | | - | 1 PCS | 49.00 |
| 1900 | Nozzle cover | including mounting material | 30000 | 0.051 lb | 84798997 | DE | S | | - | | - | 1 PCS | 157.00 |

^{*} PU = packing unit | C/O = country of origin | SL = service level (U=user, S=service | WL = warranty limitation | SNo. = serial number required | Stock = stock recommendation * WPC = wear parts and consumables | POH = parts on hand (recommended minimum quantity for on site service calls)



| Art. No. | Description | Specifications | Picture | Weight | Customs Tariff No. | C/O* | SL* | WL.* | SNo.* Stock* | WPC* | POH* | PU* | Sales price in \$ |
|----------|---|--|-----------|----------|-----------------------|------|-----|------|--------------|------|------|-------|-------------------|
| 1895 | Telescopic slides for the accessories container | including mounting materialPU 2 pieces | . 1 3 000 | 0.746 lb | 84799070 | MX | S | | - | | - | 1 PU | 98.00 |
| 1879 | Tension spring for the B-axis | including mounting material | | 0.100 lb | 85011091 | DE | S | | 1 | | - | 1 PCS | 32.00 |
| 1878 | Tool changer cover | including mounting material for use in machines with serial numbers starting with K5ID2 | | 0.050 lb | 84799070 | DE | U | | 1 | | - | 1 PCS | 43.00 |

^{*} PU = packing unit | C/O = country of origin | SL = service level (U=user, S=service | WL = warranty limitation | SNo. = serial number required | Stock = stock recommendation * WPC = wear parts and consumables | POH = parts on hand (recommended minimum quantity for on site service calls)



Pneumatical Parts

| Art. No. | Description | Specifications | Picture | Weight | Customs Tariff No. | C/O* | SL* | WL.* | SNo.* Stock | WPC* | РОН* | PU* | Sales price in \$ |
|----------|---------------------------------------|--|---------|--------------|-----------------------|------|-----|------|-------------|------|------|-------|-------------------|
| 30333 | Compressed air sensor | for use in the following machines: K5 + K5 with control unit serial no. from 28960 K5 X with control unit serial no. from 26050 | | 0.108 lb | 84799070 | DE | S | | - | | - | 1 PCS | 230.00 |
| 1888 | Dust protection vacuum sensor | | | 0.011 lb | 84799070 | DE | S | | 2 | | - | 1 PCS | 30.00 |
| 1825 | Filter element for service unit MICRO | date of manufacture of the machine from 04/2014 | | 0.004 lb | 84219990 | HU | U | | 5 | X | 2 | 1 PCS | 9.00 |
| 1922 | Plastic hose 4 mm | UL-94-certifiedPU 3 m | | 1.587 ozm | 84799070 | CZ | S | | - | | - | 1 PU | 15.20 |

^{*} PU = packing unit | C/O = country of origin | SL = service level (U=user, S=service | WL = warranty limitation | SNo. = serial number required | Stock = stock recommendation * WPC = wear parts and consumables | POH = parts on hand (recommended minimum quantity for on site service calls)



Pneumatical Parts

| Art. No. | Description | Specifications | Picture | Weight Customs Tariff No. | | SL* | WL.* SNo.* Stoc | (* WPC | * POH* | PU* | Sales price in \$ |
|----------|------------------------|---|---------|------------------------------|----|-----|-----------------|--------|--------|-------|-------------------|
| 1666 | Service unit MICRO | with water separator, manometer and pressure regulator | | 0.500 lb 84811005 | DE | U | 1 | | - | 1 PCS | 159.00 |
| 1499 | Solenoid valve MHP1-UL | for mounting at valve terminal, including – 2 screws – hose connector and plug-in connection wire – for UL certified machines – installed in S models since November 2013 | | 0.816 lb 84812090 | DE | S | 1 | | - | 1 PCS | 74.00 |

^{*} PU = packing unit | C/O = country of origin | SL = service level (U=user, S=service | WL = warranty limitation | SNo. = serial number required | Stock = stock recommendation * WPC = wear parts and consumables | POH = parts on hand (recommended minimum quantity for on site service calls)



Miscellaneous

| Art. No. | Description | Specifications | Picture | Weight | Customs Tariff No. | C/O* | SL* | WL.* | SNo.* Stock | WPC* | POH* | PU* | Sales price in \$ |
|----------|-------------------------|--|--|-----------|-----------------------|------|-----|------|-------------|------|------|-------|-------------------|
| 1725 | Calibration blank 10 mm | material PU diameter 98 mm thickness 10 mm | | 0.500 lb | 39211390 | DE | U | | 1 | X | 3 | 1 PCS | 7.50 |
| 30028 | Carrying aid K5/K5+ | including safety strap | | 11.365 lb | 84799070 | DE | U | | - | | - | 1 PCS | 242.00 |
| 1850 | Fin Food Lube | - for linear guiding - PU 250 ml safety data sheet: http://download.vhf.de | product CAS Lig. process of 1975 to 1985 process of 198 | 0.500 lb | 27101999 | NL | S | | 1 | X | 1 | 1 PCS | 64.00 |
| 1846 | Flexible crevice nozzle | | | 0.379 lb | 84799070 | MY | U | | - | | - | 1 PCS | 74.00 |

^{*} PU = packing unit | C/O = country of origin | SL = service level (U=user, S=service | WL = warranty limitation | SNo. = serial number required | Stock = stock recommendation * WPC = wear parts and consumables | POH = parts on hand (recommended minimum quantity for on site service calls)



Miscellaneous

| Art. No. | Description | Specifications | Picture Weight | T | Customs Tariff No. | C/O* | SL* | WL.* | SNo.* Stock | WPC* | РОН* | PU* | Sales price in \$ |
|----------|--------------------------------------|---|----------------|------|-----------------------|------|-----|------|-------------|------|------|-------|----------------------|
| 30059 | M5 thread insert with assembling aid | | 0.010 | lb 8 | 84799070 | DE | S | | 10 | | - | 1 PCS | 6.50 |
| 2019 | Transport lock K5 | for spindle SFK 300P | 0.220 | lb 3 | 39239000 | DE | U | | 1 | | - | 1 PCS | 41.00 |
| 1865 | White Grease | for ball screw spindles tube 150 ml safety data sheet: http://download.vhf.de | 0.500 | lb 2 | 27101999 | NL | U | | 1 | X | - | 1 PCS | 63.00 |

^{*} PU = packing unit | C/O = country of origin | SL = service level (U=user, S=service | WL = warranty limitation | SNo. = serial number required | Stock = stock recommendation * WPC = wear parts and consumables | POH = parts on hand (recommended minimum quantity for on site service calls)



Spindles and Accessories

| Art. No. | Description | Specifications | Picture We | | Customs Tariff No. | C/O* | SL* | WL.* | SNo.* St | ock* | WPC* | POH* | PU* | Sales price in \$ |
|----------|---------------------------------|--|--|--------|-----------------------|------|-----|------|----------|------|------|------|-------|-------------------|
| 1728 | Collet chuck 3 mm, rust-proof | packed separately | | 013 lb | 84661020 | DE | U | | | 2 | X | 2 | 1 PCS | 180.00 |
| 1760 | High frequency spindle SFK 300P | - high frequency spindle rotational speed 5,000 to 60,000 RPM maximum power output 500 W continuous power 300 4-fold bearing hybrid ceramic ball bearings stainless steel collet chuck including service set version with sealing air and cone cleaning including pneumatical collet chuck | 2.3 | 300 lb | 84799070 | DE | S | | X | 1 | X | 1 | 1 PCS | 4,450.00 |
| 1730 | Spindle service set | for collet chuck maintenance | SPINDLE SERVICE SET Class Class Grand Charles Str. A. Charle | 132 lb | 96039099 | DE | U | | | 1 | X | 1 | 1 PCS | 57.00 |

^{*} PU = packing unit | C/O = country of origin | SL = service level (U=user, S=service | WL = warranty limitation | SNo. = serial number required | Stock = stock recommendation * WPC = wear parts and consumables | POH = parts on hand (recommended minimum quantity for on site service calls)



Tools

| Art. No. | Description | Specifications | Picture Weig | ght | Customs Tariff No. | C/O* | SL* | WL.* | SNo.* Stock* | WPC* | POH* | PU* | Sales price in \$ |
|----------|--------------------------------|--|--------------|-------|-----------------------|------|-----|------|--------------|------|------|-------|-------------------|
| 1512 | Dial indicator with stand | with 3D articulated arm and clamp stand for true running and axis backlash measurements measuring accuracy ± 0.01 mm | 2.00 | 00 lb | 84799070 | JP | S | | - | | 1 | 1 PCS | 639.00 |
| 1841 | Digital measuring slide | measuring range 100 mm | 0.45 | 50 lb | 84799070 | CN | U | | - | | - | 1 PCS | 103.00 |
| 1655 | Digital micrometer screw gauge | 0–25 mm | 1.00 | 00 lb | 84799070 | CN | U | | 1 | | - | 1 PCS | 180.00 |
| 1731 | Drill with 3 mm shank | Ø cutting edge 2.80 mm, Ø shank 3.0 mm L cutting edge 10.5 mm, L total 38 mm with stop ring | 0.07 | 70 lb | 82075090 | DE | U | | 2 | X | 1 | 1 PCS | 7.40 |

^{*} PU = packing unit | C/O = country of origin | SL = service level (U=user, S=service | WL = warranty limitation | SNo. = serial number required | Stock = stock recommendation * WPC = wear parts and consumables | POH = parts on hand (recommended minimum quantity for on site service calls)



Tools

| Art. No. | Description | Specifications | Picture | Weight | Customs Tariff No. | C/O* | SL* | WL.* | SNo.* Stock* | WPC* | РОН* | | Sales price in \$ |
|----------|----------------------|---|---------|-----------|-----------------------|------|-----|------|--------------|------|------|-------|-------------------|
| 1824 | Service trolley case | robust trolley case for service works precise measuring equipment and high-quality tools complete kit for all vhf Impression machines | MI | 33.100 lb | 82059090 | DE | S | | - | | 1 | 1 PCS | 3,930.00 |

Please note that single articles can be used in several machine models. Our stock recommendation is intended for 1 to 20 machines per service base. We grant the standard discount for spare parts.

Warranty limitation: warranty claims can only be made if the relevant machine is inspected and repaired by vhf. Alternatively, the partner can order the part within the warranty period and exchange it at his/her own expense and liability.

Prices are list prices and do not include any discounts, tax, shipping or other charges that may apply • All purchases are subject to our Terms of Sale which can be found at www.vhf.com • Products, prices and terms are subject to change without notice • All prices exclude VAT, customs duties and transportation/packaging fees • All information given may change without further notice.

As of 02/06/2022 18